



MURALEX 12" and 16" PVC INTERLOCKING LINER PANELS

The smooth, tough, cost-effective solution for interior walls and ceilings

Easy to work with and to install, Muralex by Vicwest is a PVC liner panel, available in 12" and 16" widths, perfect for the interior walls or ceilings in your agricultural, commercial or industrial buildings. The smooth, yet resistant surface is the ideal solution for many applications where you require a tough, chemically resistant interior. The interlocking system makes it easy to install using common tools and basic installation skills. Durable and versatile, Muralex comes with an outstanding 20 Year limited warranty.

APPLICATIONS:

- Hog, poultry and dairy buildings
- Car wash bays
- Farm storage buildings
- Chemical processing & storage facilities
- Refrigerated warehouses
- Residential garages

See reverse side for complete details and specifications



QUALITY FARM BUILDING PRODUCTS

vicwest.com

Clean-up is a breeze
using conventional pressure
washing equipment

MURALEX 12" and 16" PVC INTERLOCKING LINER PANELS

The smooth, tough, cost-effective solution for interior walls and ceilings

Need a smooth surface with impact resistance and washability in a cost effective solution?

Owners of agricultural, commercial and light industrial buildings choose Muralex by Vicwest for the smooth, impact resistant and washable surface.

Features and Benefits:

- 12" and 16" PVC flat profile panels with coordinating trims and corners
- The economical alternative to other interior panel systems
- Can be used for both walls and ceilings
- Attractive high-gloss white finish giving superior light reflectance
- Extremely light weight – very high strength to weight ratio
- Excellent impact resistance – resists breaking, scuffs and scratches
- Easy to clean
- Easy to install using common equipment
- Hidden fastener system eliminates unsightly areas where dirt and bacteria can collect
- Excellent chemical resistance
- Will not corrode
- 20 Year Limited Warranty against deterioration, loss of rigidity
- Complements our AgTUF line of interior products

Specifications:

- 12" and 16" x ½" panels in standard lengths (8' 6", 10', 12' & 16' lengths)
- Min. length = 1 ft.
Max. length = 20 ft.
- Weight per panel = 1 lb per square foot
- Hidden fastener system using a pre-punched screw
Nail flange - Can be screwed, stapled or nailed
For best results, a stainless steel screw is recommended
- Can be installed directly on a flat surface (wall or ceiling) or on studs
- Can support insulation

Coordinating trims
and corners



QUALITY FARM BUILDING PRODUCTS

Note: For more information about building with steel, please refer to the CSSBI publication on the structural integrity of steel building panels. In accordance with ongoing efforts to improve our products and their performance, Vicwest Building Products reserve the right to change without notice the specifications contained herein. The contents herein are for general information and illustrative purposes only and are not intended to serve as any type of advice. Every effort is made to ensure the accuracy of the information included in this brochure and it is believed that the information contained herein is accurate and reliable as of the date of publication. Vicwest Building Products does not warrant or represent the accuracy or reliability of any information included in this brochure. Any reliance on any information without consultation with Vicwest Building Products or a duly authorized representative shall be at the user's own risk.